

# PKP-2600-SI-FR



DESIGN YOUR OWN  
PROTOTYPE ONLINE



CANopen  
J1939



## FLEXIBLE - SMART - RUGGED

**PKP-2600-SI-FR** is a compact keypad based on CAN protocol. It comes equipped with twelve keys. The keypad is water and dust resistant, and can be installed both inside and outside the cockpit. The PKP-SI-FR (full rubber) Series has a solid rubber key face instead of a removable insert. It is a production based unit where the icon design remains the same, saving installation time not having to populate inserts. The PKP-SI-FR Series also allows for a larger surface area for the icon from 14mm dia to an increased 18mm dia.

### SOFTWARE FEATURES

**CAN and RS485 Keypad Addresses** – Assign any valid CAN and RS485 address to the keypad. Communicate on either BUS simultaneously.

**J1939 Address Claim Transmission** – Keypads no longer have to be pre-programmed to a specific address. This enables customers that work in applications in the field without access to a GUI to use any replacement keypad on-hand. The keypad can be configured to automatically announce its address and accept a new address assignment as appropriate.

**Event Status Transmission** – The keypad can send messages to the BUS indicating a button press or a button release event has occurred. This confirmation allows digital systems to have the same input acknowledgements as that of the latching position of a mechanical switch.

**Periodic Status Transmission** – The keypad sends a continuous broadcast of messages indicating the press or release status of each button at that instance. The frequency of these messages can be adjusted in a wide range.

**Periodic Heartbeat** – The keypad sends a continuous broadcast of messages indicating it is functioning correctly. The frequency of these messages can be adjusted in a wide range.

**CANopen Communications Protocol** – Fully compliant with Device Profile 401d.


### HARDWARE FEATURES

**IP67/IP69K waterproof rating** – Guaranteed to be dust tight and sealed against water immersion to a depth of 1 meter for up to 1 hour. The IP69K rating provides protection against high pressure water at high temperature spray downs.

**UV Protected** – UVB 400 hours: Keypad is highly resistant to deterioration caused by exposure to sunlight.

**A membrane compensation valve** which self compensate the internal pressure within the keypad, alleviating mechanical stresses that can be produced by shifts in external temperatures.

**The keypad's symmetrical design** and spacing between keys makes it easier to install multiple keypads alongside one another.



Icons shown on this keypad are for visual demonstration only.

## STANDARD FEATURES

- Reconfigurable keys
- LED state & status configurable
- Vertical or horizontal mount
- LED backlit icons
- Multicolor indicator rings
- Laser etched icons
- ON/OFF, momentary, toggle & scroll
- Hundreds of stock icons to choose from

## SOFTWARE FEATURES

- Change CAN or RS485 keypad addresses independently
- Periodic status transmission
- Heartbeat
- Event status transmission
- LED acknowledgement
- Address claim transmission
- RS485, CANopen and J1939

## OTHER BENEFITS

- Programmer's manual available to help support plug-and-play reconfigurability




## SPECIFICATIONS FOR STANDARD KEYPADS

### ELECTRICAL

|                   |  |
|-------------------|--|
| Supply Voltage    | 12-24Vdc Nominal (8-32VDC)   |
| Standby Current   | <50 mA   |
| Communication BUS | RS485, CANopen, J1939  |
| MTBF              | 204291 hours [in accordance with MIL-HDBK-217 - operating environment Ground Mobile] |

### MECHANICAL

|                           |   |
|---------------------------|---|
| Connector                 | Deutsch DT04-4P   |
| Switch Life               | 3 million operations  |
| Mounting Studs            | #10-32 CDA-510 phosphor bronze, electroplated bright tin  |
| Keypad                    | Silicone rubber with polyurethane hardcoat  |
| PC Board                  | 1,6mm thick, Nema Grade FR-4, double clad with 1oz copper   |
| Operating Temperature     | -40°C to +70°C  |
| Storage Temperature       | -40°C to +85°C  |
| Thermal Shock             | -40°C to +85°C According to table 2 of ISO16750-4   |
| UV Protection             | UVB 400 hours   |
| Salt Spray                | Per ASTM B117   |
| Chemical Resistance       | Deet, Engine Cleaner, Isopropyl Alcohol, Suntan Lotion, Multi-Purpose Cleaner, Orange Citrus Cleaner, Muriatic Acid |
| Ingress protection Rating | IP67/IP69K  |
| Weight                    | 230 gr  |



**blink**

M A R I N E

Blink S.r.l.


Via Montefeltro, 6 - 20156 Milano - Italy

Tel. +39 02 3088583 - Fax +39 02 33406697

[www.blinkmarine.com](http://www.blinkmarine.com) - [info@blinkgroup.com](mailto:info@blinkgroup.com)

[WARNING] IMPROPER SELECTION, IMPROPER USE AND/OR FAILURE OF THE BLINK SYSTEMS PRODUCTS DESCRIBED HEREIN OR RELATED ITEMS CAN CAUSE DEATH, PERSONAL INJURY AND PROPERTY DAMAGE. This document and other information from Blink, provide product and/or system options for further investigation by users having technical expertise. It is important to analyze all aspects of the application, including consequences of any failure. Due to the variety of operating conditions and applications for these product(s), the manufacturer of the application is solely responsible for marking the final selection of the product(s) and assuring that all performance, safety and warning requirements of the application are met. The products described herein, including without limitation, product features, specifications, designs, availability and pricing, are subject to change by Blink at any time without notice.

## CONNECTOR STANDARD PINOUT



WIRE SIDE

| PIN | COLOUR | FUNCTION         |
|-----|--------|------------------|
| 1   | Blue   | CAN L            |
| 2   | White  | CAN H            |
| 3   | Black  | Negative battery |
| 4   | Red    | Vbatt. (12-24V)  |

The one illustrated above is the standard pinout; however, some keypads may be supplied with alternative pinouts or connectors.